

Electromagnetic metering pumps

High resolution & ultra compact



DC power voltage / vertically- or horizontally- oriented pump head

The HRP series is powered by 12VDC or 24VDC and offers an ideal fit for built-in applications. Select vertically- or horizontally-oriented pump head to get optimum mounting position in various host machines.

High resolution

Digitally-controlled spm range is 0-720spm. The minimum flow of 0.055ml per shot offers a constant imperceptible injection.

Waterproof and dustproof structure

The sealed drive unit and control unit are enclosed to a water/dust-proof rating of IP65.

- This pump is not completely water resistant. Protect the pump with a cover when installing it out of doors.

Operational function

HRP pumps are controlled by an external signal and are available in the following types.

Pulse control type

A pulse signal input controls pump operation (stroke rate). The pump makes one shot per pulse synchronously.

- An input signal is required to enable operation in addition to power activation for this type.
- The pump can not exceed a maximum of 720spm, even if the external signal input instructs the pump to run beyond that speed.

4-20mA control type

The input of 4-20mA proportionally controls the pump operation (stroke rate).

- An input signal is required to enable operation in addition to power activation for this type.

1-5V control type

The input of 1-5V proportionally controls the pump operation (stroke rate).

- An input signal is required to enable operation in addition to power activation for this type.

Stop control type

The input of the stop signal suspends the pump operation.

- The type of pump starts to run at 720spm upon power activation.


Optional air vent valves are available.

Pat. Pend.

JAPAN



Wet end materials



	1 Pump head	2 Valve seat	3 Valve	4 Gasket	5 O ring	6 Diaphragm	7 Valve spring
Materials	PVDF	FKM	Alumina ceramic	PTFE	FKM	PTFE+EPDM	PEEK

• Valve spring is HRP-54H only. • EPDM is not a wet end. • Contact us for other valve seat, valve and O ring materials.

Identification

HRP - 5 4 V - 1 P 1 - □□

- Series name**
- Drive unit**
(Average power consumption)
5: 5.6W
- Discharge capacity**
4: 38mL/min
- Pump head**
V: Vertically oriented
H: Horizontally oriented
- Power voltage**
1: 12VDC
2: 24VDC
- Special version**
- Connection bore**

No.	Tube connection bore
1	Ø3×Ø6
2	Ø4×Ø6
3	Ø1/8"×Ø1/4"
- Control method**
P: Pulse control
A: 4-20mA control
V: 1-5V control
S: Stop control

Specification

Pump & Drive units

Model	flow rate mL/min	Max. discharge pressure MPa	Stroke rate spm	Tube connection bore	Power voltage V	Power consumption W	Current value A	Weight kg
HRP-54V/H-1	38	0.2	0 - 720	3mm×6mm, 4mm×6mm, 1/8"×1/4"	DC12	5.6	1.5	0.5
HRP-54V/H-2					DC24		1.0	

- This specification is based on pumping ambient clean water at rated voltage.
- Flow rate is collected at the maximum discharge pressure and 720spm. The flow rate increases as a discharge pressure decreases.
- 0.12MPa or more discharge pressure is needed to prevent over feeding. If the discharge pressure is at or below the required MPa, install a check valve or back pressure valve.
- Allowable room temperature: 0 - 40 °C • Allowable liquid temperature: 0 - 40 °C • Allowable voltage deviation: ±5% of the rated voltage **12VDC: 11.4V - 12.6V, 24VDC: 22.8V - 25.2V**

Control unit

Control type	Upper limit spm	Operation	Input signal	Control type	Upper limit spm	Operation	Input signal	
Pulse control type	720spm	One shot per signal (Synchronous operation) ^{Note2}	No-voltage contact or open collector ^{Note1}	1 - 5V control type	720spm	1-5VDC proportional operation to 0-720spm	Voltage: 1-5VDC (Current capacity of 25mA or more)	
	720spm	4-20mADC proportional operation to 0-720spm	Current: 4-20mADC		Stop control type	720spm (Fixed)	The pump stops during contact input.	No-voltage contact or open collector ^{Note1}
	720spm	4-20mADC proportional operation to 0-720spm	Current: 4-20mADC			720spm (Fixed)	The pump stops during contact input.	No-voltage contact or open collector ^{Note1}


Note1: The maximum applied voltage to the contact is 12V at 5mA. When using a contact type relay, the minimum application load should be 5mA or below.

Note2: The external pulse signal is entered to run the pump over the upper limit spm, the signal is cancelled.

Power cable

Conduction section area	0.32 mm ² (Triplex cable)	Standard	UL3265
Length	600 mm	Terminal treatment	Bared

Dimension (mm)



Model	W	H	L	a	b	c	d	e	f	g	i	j	k	m	n	o
HRP-54V	62	—	(101)	(19)	27	(73)	22.5	(25)	4	9.5	51.5	4.5	10	6	—	—
HRP-54H		(51.5)	(122)	—		—		(56)								

www.iwakipumps.jp

IWAKI CO.,LTD. 6-6 Kanda-Sudacho 2-chome Chiyoda-ku Tokyo 101-8558 Japan TEL : (81)3 3254 2935 FAX : 3 3252 8892

EUROPE / U.S.A.

European office : IWAKI Europe GmbH TEL: (49)2154 9254 0 FAX: 2154 9254 48
Austria : IWAKI (Austria) GmbH TEL: (41)26 674 93 00 FAX: 26 674 93 02
Belgium : IWAKI Belgium N.V. TEL: (32)13 67 02 00 FAX: 13 67 20 30
Denmark : IWAKI Nordic A/S TEL: (45)48 24 2345 FAX: 48 24 2346
Finland : IWAKI Suomi Oy TEL: (358)9 2745810 FAX: 9 2742715
France : IWAKI France S.A. TEL: (33)1 69 63 33 70 FAX: 1 64 49 92 73
Germany : IWAKI Europe GmbH TEL: (49)2154 9254 50 FAX: 2154 9254 55
Holland : IWAKI Holland B.V. TEL: (31)547 293 160 FAX: 547 292 332
Italy : IWAKI Italia S.R.L. TEL: (39)02 990 3931 FAX: 02 990 42888
Norway : IWAKI Norge AS TEL: (47)66 81 16 60 FAX: 66 81 16 61
Spain : IWAKI Iberica Pumps, S.A. TEL: (34)943 630030 FAX: 943 628799
Sweden : IWAKI Sverige AB TEL: (46)8 511 72900 FAX: 8 511 72922
Switzerland : IWAKI (Schweiz) AG TEL: (41)26 674 93 00 FAX: 26 674 93 02
U.K. : IWAKI Pumps (UK) Ltd. TEL: (44)1743 231363 FAX: 1743 366507
U.S.A. : IWAKI America Inc. TEL: (1)508 429 1440 FAX: 508 429 1386

ASIA / OCEANIA

Australia : IWAKI Pumps Australia Pty Ltd. TEL: (61)2 9899 2411 FAX : 2 9899 2421
China : TEL: (86)21 6272 7502 FAX: 21 6272 6929
Hong Kong : IWAKI Pumps Co., Ltd. TEL: (852)2607 1168 FAX: 2607 1000
Shanghai : IWAKI Pumps (Shanghai) Co., Ltd. TEL: (86)20 8435 0603 FAX: 20 8435 9181
Guangzhou : GFTZ IWAKI Engineering & Trading Co., Ltd. TEL: (86)10 6442 7713 FAX: 10 6442 7712
Beijing : GFTZ Iwaki Engineering & Trading Co., Ltd. (Beijing office) TEL: (82)2 2630 4800 FAX: 2 2630 4801
Korea : IWAKI Korea Co.,Ltd. TEL: (60)3 7803 8807 FAX: 3 7803 4800
Malaysia : IWAKIm Sdn. Bhd. TEL: (65)6316 2028 FAX: 6316 3221
Singapore : IWAKI Singapore Pte Ltd. TEL: (62)21 6906606 FAX: 21 6906612
Indonesia : IWAKI Singapore (Indonesia Branch) TEL: (886)2 8227 6900 FAX: 2 8227 6818
Taiwan : IWAKI Pumps Taiwan Co., Ltd. TEL: (66)2 322 2471 FAX: 2 322 2477
Thailand : IWAKI (Thailand) Co.,Ltd. TEL: (84)613 933456 FAX: 613 933399
Vietnam : IWAKI Pumps Vietnam Co., Ltd.

()Country codes

⚠ Caution for safety use: Before use of pump, read instruction manual carefully to use the product correctly.

Actual pumps may differ from the photos. Specifications and dimensions are subject to change without prior notice. For further details please contact us.

⚠ Legal attention related to export.

Our products and/or parts of products fall in the category of goods contained in control list of international regime for export control. Please be reminded that export license could be required when products are exported due to export control regulations of countries.